DSS le rössle f055 össle f055 le rössle















issle **[055] e** rössle



**RÖSSLE AG**, Johann-Georg-Fendt-Straße 50, D-87616 Marktoberdorf Phone +49 (0) 8342 2314, Fax +49 (0) 8342 95482, info@roessle.ag, **www.roessle.ag** 

Please note that all deliveries and services are subject to the terms and conditions of our company.

These are available to download on our website under www.nature-stone.de or under www.der-saubere-teich.de

All prices additionally delivery, Nov. 2017



## rössle

Technology for clean ponds





# MAINSTREAM cleaning ponds

With its strong appearance and optimized technology the MAINSTREAM represents a new direction in the compact class of pond suction cleaners. Sediment, sludge and weed as well as leaves and small stones can be powerfully and continuously sucked up out of a water depth of up to 2.5 meters. The MAINSTREAM separates out the larger materials into a bag-shaped net at the entry to the tank and expels the rest into the discharge hose using the integrated waste water pump. Weighing just 19 kilos, with robust handles and large wheels, the MAINSTREAM is an agile assistant for your pond. Complete and fully equipped, the Mainstream offers you right from the start a tool which can also be used for larger ponds.

#### MAINSTREAM - a stream like a dream

#### Technical

data:

- Suction capacity
- Suction turbine Waste water pump
- Suction hose and discharge hose

7000 l/h 1400 Watt 900 Watt

19 kg each 10m / ø 38mm

**545,38** € (plus VAT)

**649,00 €** (incl. VAT)

Item MAI1000

Included in the price:

**MAINSTREAM** 

Telescopic rod 1.5 m - 4.5 m

Suction hose 10 m TRIFLEX brush

Discharge hose 10 m Suction nozzle ø 38 mm

### The standard accessory



The universal suction nozzle sucks up coarse dirt in the "main stream".



The TRIPLEX brush is a completely new concept. The rotatable round corner brushes combined with the flexible side brushes, which follow the contours of the floor, help you to clean more effectively and efficiently.



Discharge hose ø 38 mm, 10 m



The telescopic rod is secured against twisting and can be extended using a press button to various lengths reaching from 1.5 up to an impressive 4.5 meters. The handling is improved by an ergonomic handle and the strengthened profile of the telescopic rod.

